





# CERTIFICATE

No. Z1A 014478 0005 Rev. 00

#### Holder of Certificate:

#### Kluitmann Industrietechnik Handels GmbH

Im Hammereisen 17 A 47559 Kranenburg GERMANY

**Certification Mark:** 



**Product:** 

#### Wrench Handwheel wrench

Tested according to:

PPP 52344B:2020 AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.:

034-713300490-000

Valid until:

2028-10-08

Date, 2023-10-23

-Sull

(Lutz Langguth)

## **CERTIFICATE** No. Z1A 014478 0005 Rev. 00

NO. Z1A 014478 0005 Rev. 00

### Model(s): SIGA®

#### Parameters:

	Design A length	Design B, C, D length	weight	Suitable for handwheel diameter
	[approx. mm]	[approx. mm]	[approx. g]	[mm]
Size 00	260	300	200	10 - 50
Size 0	270	310	360	25 - 80
Size 1	330	370	600	50 - 100
Size 2	440	480	1000	125 - 250
Size 3	560	590	1600	250 - 400
Size 4	765	800	2150	350 - 900

- Design A: painted red, material S355 MC 1.0976
- Design B: painted red, with rubber handle and protection against extension, material S355 MC 1.0976
- Design C: bronze coating, with rubber handle and protection against extension, material S355 MC 1.0976
- Design D: uncoated, with rubber handle and protection against extension, material CuAl10Ni5Fe5, 2.0975